


FASTENERS

PUSH RIVETS NYLON

Part No.		Dia. (mm)	Panel Thickness (mm)
Black	White		
12230	12231	2.0	0.6 – 1.2
12232	12233	2.0	1.3 – 2.0
12234	12235	2.0	2.1 – 2.8
12236	12237	2.0	2.9 – 3.6
12238	12239	2.0	3.7 – 4.4
12240	12241	2.0	4.4 – 5.0
12242	12243	2.5	1.0 – 2.0
12244	12245	2.5	2.0 – 3.0
12246	12247	2.5	2.7 – 3.6
12248	12249	2.5	3.4 – 4.3
12250	12251	2.5	4.3 – 5.2
12252	12253	2.5	5.1 – 6.0
12254	12255	3.0	1.0 – 2.0
12256	12257	3.0	2.0 – 4.0
12258	12259	3.0	3.0 – 4.0
12260	12261	3.0	4.0 – 5.0
12262	12263	3.0	5.0 – 6.0
12264	12265	3.0	5.5 – 6.5
12266	12267	3.0	6.5 – 7.5
12268	12269	3.0	7.5 – 8.5
12270	12271	3.5	1.2 – 2.1
12272	12273	3.5	2.1 – 3.0
12274	12275	3.5	2.7 – 3.6
12276	12277	3.5	3.0 – 4.0
12278	12279	3.5	3.7 – 4.6
12280	12281	3.5	4.5 – 5.5
12282	12283	3.5	5.5 – 6.5
12284	12285	4.0	2.4 – 3.4
12286	12287	4.0	3.5 – 4.5
12288	12289	4.0	4.5 – 5.5
12290	12291	4.0	5.5 – 6.5
12292	12293	4.0	6.5 – 7.5
12294	12295	4.0	7.5 – 8.5
12296	12297	4.0	9.0 – 10.5
12298	12299	5.0	1.5 – 3.5
12300	12301	5.0	2.5 – 3.5
12302	12303	5.0	3.5 – 4.5
12304	12305	5.0	4.5 – 5.5
12306	12307	5.0	5.5 – 6.5
12308	12309	5.0	6.5 – 7.5
12310	12311	5.0	7.5 – 8.5
12312	12313	6.0	2.5 – 4.0
12314	12315	6.0	3.5 – 5.5
Also available in other colours - call for quotation			

Nylon Push Rivets are an economical, reusable method of securing parts together.



To use simply place rivet into pre-drilled hole and push head to secure. Lift head to unsecure and remove, rivets can be re-used.



Nylon Push Rivets resist corrosion and provide electrical protection.