

# STANDARD AUTOMOTIVE BLADE FUSE CLIPS & HOLDERS

## FOR .205 (5.2) × .025 (.64) STANDARD BLADE FUSES

For Littelfuse ATO 257 series/Bussmann ATC series or equivalent

- Thru hole PC mountable, maintains position during wave soldering
- Holder design prevents solder wicking
- Withstands the rigors of shock and vibration
- Holds fuse securely, even after multiple insertions

### VERTICAL FUSE ENTRY


#### SPECIFICATIONS

**Contacts:** .016 (.41) thick Brass, Tin Nickel Plate



**Insulator:** Glass filled Nylon, UL Rated 94V-0

**Current Rating:** 30 Amps @ 500V AC

**Temperature Rating:** -58°F to +292°F (-50°C to +145°C)



Mounting Detail For Two Clips



3522-2

3522-3

CAT. NO. 3522-2

CAT. NO. 3522-3

CAT. NO. 3522

### HORIZONTAL FUSE ENTRY

- Designed for low height clearance applications
- Fuse will be inserted parallel to board
- Thru hole PC mountable, maintains position during wave soldering
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time
- Polarized legs assure proper orientation of clips onto board


#### SPECIFICATIONS

**Contacts:** .012 (.30) thick Brass, Tin Nickel Plate



**Insulator:** PBT, UL Rated 94V-0

**Current Rating:** 30 Amps @ 500V AC

**Temperature Rating:** -58°F to +292°F (-50°C to +145°C)



Mounting Detail For Two Clips




CAT. NO. 3550-2

CAT. NO. 3550


### 2 IN 1 FUSE HOLDER

For Littelfuse ATO 257 series/Bussmann ATC series, Littelfuse Low Profile Mini 897 series or equivalents

- Accepts Standard Auto Fuses or Low Profile Mini Fuses
- Low insertion force
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time
- Thru hole PC mountable, maintains position during wave soldering




Mounting Detail




### UNIVERSAL CLIP

For Littelfuse ATO 257 series/Bussmann ATC series, Littelfuse Mini 297 or 997 series/Bussmann ATM series, Littelfuse Low Profile Mini 897 series or equivalents


- Accepts most Auto-Blade Fuses
- Low insertion force
- Thru hole PC mountable, maintains position during wave soldering



Mounting Detail for Standard Auto Fuses and Low Profile Mini Fuse



Mounting Detail for Mini Fuse



#### SPECIFICATIONS

**Contacts:** .016 (.41) thick Brass, Tin Nickel Plate

**Current Rating:** 20 Amps @ 500V AC

**Temperature Rating:** -58°F to +292°F (-50°C to +145°C)

CAT. NO. 3557-2

CAT. NO. 3557

Marking

"AUTO" FUSE CLIPS & HOLDERS

O.D.