

## Nylon Push Rivets

Part No.		Diam. (mm)	Panel Thickness (mm)
Black	White		
12230	12231	2.0	0.6 – 1.2
12232	12233	2.0	1.3 – 2.0
12234	12235	2.0	2.1 – 2.8
12236	12237	2.0	2.9 – 3.6
12238	12239	2.0	3.7 – 4.4
12240	12241	2.0	4.4 – 5.0
12242	12243	2.5	1.0 – 2.0
12244	12245	2.5	2.0 – 3.0
12246	12247	2.5	2.7 – 3.6
12248	12249	2.5	3.4 – 4.3
12250	12251	2.5	4.3 – 5.2
12252	12253	2.5	5.1 – 6.0
12254	12255	3.0	1.0 – 2.0
12256	12257	3.0	2.0 – 3.0
12258	12259	3.0	3.0 – 4.0
12260	12261	3.0	4.0 – 5.0
12262	12263	3.0	5.0 – 6.0
12264	12265	3.0	5.5 – 6.5
12266	12267	3.0	6.5 – 7.5
12268	12269	3.0	7.5 – 8.5
12270	12271	3.5	1.2 – 2.1
12272	12273	3.5	2.1 – 3.0
12274	12275	3.5	2.7 – 3.6
12276	12277	3.5	3.0 – 4.0
12278	12279	3.5	3.7 – 4.6
12280	12281	3.5	4.5 – 5.5
12282	12283	3.5	5.5 – 6.5
12284	12285	4.0	2.4 – 3.4
12286	12287	4.0	3.5 – 4.5
12288	12289	4.0	4.5 – 5.5
12290	12291	4.0	5.5 – 6.5
12292	12293	4.0	6.5 – 7.5
12294	12295	4.0	7.5 – 8.5
12296	12297	4.0	9.0 – 10.5
12298	12299	5.0	1.5 – 3.5
12300	12301	5.0	2.5 – 3.5
12302	12303	5.0	3.5 – 4.5
12304	12305	5.0	4.5 – 5.5
12306	12307	5.0	5.5 – 6.5
12308	12309	5.0	6.5 – 7.5
12310	12311	5.0	7.5 – 8.5
12312	12313	6.0	2.5 – 4.0
12314	12315	6.0	3.5 – 5.5



Economical and reusable, these nylon rivets resist corrosion, provide electrical protection and a clean, finished look.

Removable Nylon Push Rivets (also called “Snap Rivets”) easily snap into mounting holes with fingertip pressure. Similarly, these parts are easily removed by simply pulling the head up.

During installation, the rivet legs expand to securely lock components into place.

Available in 43 sizes, diameters range from 2 mm to 6 mm. Panel thickness ranges from a minimum of 0.6 mm up to a maximum of 10.50 mm.

Standard parts come in black or white colour, other colours can be made to order for larger quantity requirements.

**Material:**

Nlon 6/6

**UOM:**

Sold in units of 100.