


NPA PTY LTD



Rivet - Push - Nylon 66 - WHITE





Part No.	Diameter (mm)	Panel Thickness (mm)	
12231	2.0	0.6 – 1.2	
12233	2.0	1.3 – 2.0	
12235	2.0	2.1 – 2.8	
12237	2.0	2.9 – 3.6	Nylon Push Rivets are an economical, reusable method of securing parts together. To use simply place rivet into pre-drilled hole and push head to secure. Lift head to unsecure and remove, rivets can be re-used.
12239	2.0	3.7 – 4.4	
12241	2.0	4.4 – 5.0	
12243	2.5	1.0 – 2.0	
12245	2.5	2.0 – 3.0	
12247	2.5	2.7 – 3.6	
12249	2.5	3.4 – 4.3	
12251	2.5	4.3 – 5.2	
12253	2.5	5.1 – 6.0	
12255	3.0	1.0 – 2.0	
12257	3.0	2.0 – 3.0	
12259	3.0	3.0 – 4.0	Nodes Book Bisses as size as as
12261	3.0	4.0 – 5.0	Nylon Push Rivets resist corrosion and provide electrical protection.
12263	3.0	5.0 – 6.0	
12265	3.0	5.5 – 6.5	
12267	3.0	6.5 – 7.5	
12269	3.0	7.5 – 8.5	
12271	3.5	1.2 – 2.1	
12273	3.5	2.1 – 3.0	
12275	3.5	2.7 – 3.6	



NPA PTY LTD



Part No.	Diameter (mm)	Panel Thickness (mm)	
12277	3.5	3.0 – 4.0	
12279	3.5	3.7 – 4.6	
12281	3.5	4.5 – 5.5	
12283	3.5	5.5 – 6.5	Nylon Push Rivets are an eco- nomical, reusable method of securing parts together.
12285	4.0	2.4 – 3.4	
12287	4.0	3.5 – 4.5	
12289	4.0	4.5 – 5.5	
12291	4.0	5.5 – 6.5	To use simply place rivet into pre-drilled hole and push head
12293	4.0	6.5 – 7.5	to secure. Lift head to unsecure and re-
12295	4.0	7.5 – 8.5	move, rivets can be re-used.
12297	4.0	9.0 – 10.5	
12299	5.0	1.5 – 3.5	
12301	5.0	2.5 – 3.5	
12303	5.0	3.5 – 4.5	
12305	5.0	4.5 – 5.5	N. dan Bunk Birata maiat arms
12307	5.0	5.5 – 6.5	Nylon Push Rivets resist corro- sion and provide electrical pro- tection.
12309	5.0	6.5 – 7.5	tection.
12311	5.0	7.5 – 8.5	
12313	6.0	2.5 – 4.0	
12315	6.0	3.5 – 5.5	