# **SCREWS, BOLTS, & THREADED ROD**



#### THREADED ROD

This versatile threaded rod stock is easily cut to size, resistant to most chemicals, electrically insulating, non-magnetic, lightweight, low thermal conductivity, vibration and abrasion resistant.

Stock length is 2 feet. Longer lengths up to 8 feet available on special order.

We can cut to your length requirement with a nominal cutting charge.

Other plastic materials can be furnished on special order.

Request quote.



PVC (Polyvinyl Chloride) is an amorphous thermoplastic material with excellent chemical resistance and dielectric properties. Good tensile, flexual and mechanical strength, low moisture absorption, exceptional dimensional stability and good flammability characteristics. Maximum service temperature 140° F. PVC has a good high strength to weight ratio. Rated UL94VO. Dark gray color. Stock lengths; 2 FT, 4 FT, 6 FT, and 8 FT. Special lengths can be cut to your length requirement for a nominal cutting charge. Please request quote.



### **PVC THREADED RODS**

#### **Molded in Natural PVC**

PART NUMBER	SCREW SIZE	THREAD
3800440TRPVC	4	440
3800632TRPVC	6	632
3800832TRPVC	8	832
3801024TRPVC	10	1024
3801032TRPVC	10	1032
3825020TRPVC	1/4	1/4-20
3831218TRPVC	5/16	5/16-18
3837516TRPVC	3/8	3/8-16
3850013TRPVC	1/2	1/2-13
3862511TRPVC	5/8	5/8-11
3875010TRPVC	3/4	3/4-10
3887509TRPVC	7/8	7/8-9
3810008TRPVC	1	1-8

## **NYLON THREADED RODS**

#### **Molded in Natural Nylon 6/6**

PART NUMBER	SCREW SIZE	THREAD
3800440TR	4	440
3800632TR	6	632
3800832TR	8	832
3801024TR	10	1024
* 3801032TR	10	1032
* 3825020TR	1/4	1/4-20
* 3831218TR	5/16	5/16-18
* 3837516TR	3/8	3/8-16
* 3850013TR	1/2	1/2-13
3862511TR	5/8	5/8-11
3875010TR	3/4	3/4-10
3887509TR	7/8	7/8-9
3810008TR	1	1-8

<sup>\*</sup> These sizes are available in natural Acetal material, contact sales for price.