

Cable Gland - CM - PG Thread - Crude BRASS



Part No.	Identification	Thread	Min. Cable Size (mm ²)	Max. Cable Size (mm ²)	Thread Length (mm)	Nut Width (mm)	Head Width (mm)	
DEL2001	CM6	PG-7	3	6	6.5	15	13	
DEL20010	CM6 long	PG-7	3	6	15	15	13	
DEL2002	CM8	PG-9	6	8	7	19	17	
DEL20020	CM8 long	PG-9	6	8	15	19	17	
DEL2003	CM10	PG-11	8	10	7	22	19	
DEL20030	CM10 long	PG-11	8	10	15	22	19	
DEL2004	CM12	PG-13	10	12	8	24	22	
DEL20040	CM12 long	PG-13	10	12	15	24	22	
DEL2005	CM14	PG-16	12	14	8	27	24	
DEL20050	CM14 long	PG-16	12	14	15	27	24	
DEL2006	CM18	PG-21	14	18	8	32	30	
DEL20060	CM18 long	PG-21	14	18	15	32	30	
DEL2007	CM24	PG-29	18	24	8	41	41	
DEL20070	CM24 long	PG-29	18	24	15	41	41	
DEL2008	CM30	PG-36	24	30	8	55	50	
DEL2009	CM30 long	PG-36	24	30	15	55	50	
DEL2010	CM35	PG-42	30	35	10	60	55	
DEL2011	CM35 long	PG-42	30	35	15	60	55	
DEL2012	CM40	PG-48	35	40	10	65	60	
DEL2013	CM40 long	PG-48	35	40	15	65	60	
DEL2014	CM50	PG-2 1/2"	40	50	18	80	80	
DEL2015	CM60	PG-3"	40	60	20	100	90	
DEL2016	CM80	PG-4"	60	80	25	125	115	

Temp. Range: -40°C to 120°C
 Rating: IP 66
 Standards: NFC 68312